



**Product name : Plate magnet for iron separation (waterproof) 350x60x40 / N**

## PERFORMANCE PARAMETERS

Manufacturer	Enes Magnesy
Length	350 [mm]
* Magnetic section length	300 [mm]
Width	60 [mm]
Height	40 [mm]
With mounting hole	gwintowanym
Thread type	internal
Thread length	10 [mm]
Thread size	M10
Magnet type	Neodymium
polarity	biegunu naprzemienne
Maximum working temperature	≤ 80 °[C]
Housing	stainless steel, AISI 304 / EN 1.4301, approved for contact with food
water-resistant	yes
Waterproof	class IP67
Przesypowy	yes
Zasypowy	yes
hunged	yes
Range	max. 120 [mm]
work in systems with the flow of purified material	grawitacyjnym
Weight	5.5 [kg]

A plate magnet mounted above a belt conveyor is used for catching of undesirable steel or iron elements from transported substances (food industry, processing of plastics, mineral raw materials, recycling, etc.). Mounted at a angle, can also be used as a chute separator. Watertight housing made of acid-proof steel AISI 304 / EN 1.4301 contains a magnetic circuit with neodymium magnets. It is a bottom surface of the beam which is magnetic active. Both ends are equipped with two threaded apertures M10 (spaced 38 mm) for mounting.

**On commission we are ready to provide magnetic separators with dimensions chosen by Clients. Magnetic parameters, range of activity and dimensions are adjusted according to Client needs and expectations.**

**Magnetic field** in the center of surface between the magnetic poles (maximum) is ~0,7 [T] = 7000

[Gs].

As an example, range of catching for different caught objects: balls Ø5-10 - approx.70 mm, screw caps M5-M10 - approx.80 mm, flat spanner - approx.100 mm, iron nails 2"-3,5" - approx.120mm.

In the plate magnet sintered neodymium magnets were used. The maximal working temperature for the magnetic separators with neodymium magnets is approx. **80°C**.

Weight: ~5,5 [kg]

**Caution! A careless handling can cause serious injury to hands !**



## TECHNICAL DRAWING

